



AB  
07

## Electrical

Input voltage/Frequency: 220-253V 50 Hz

Rated power: 1600 W

Motor type: Dyson digital motor – brushless DC Motor

Motor switching rate: 6,000 per second

Motor speed: 90,000 rpm

Operating temperature range: 0°– 40°C

Heater type: None

Standby power consumption: Less than 0.5 W

## Construction

Casing construction: Polycarbonate-ABS casing

Antimicrobial coating type: Antimicrobial moulded additive in fascia and blades

Bacterial reduction rate from external surfaces: Up to 99.9% over 24 hours

Colour finish: Grey or White

Light reflective value: 28.3 (grey) 77.4 (white)

Galvanised steel back plate/mounting bracket

Exterior screw type: Anti-tamper M6 machine screw

Water ingress protection to IPX5

## Filter

HEPA filter (glass fibre and fleece prelayer)

Bacteria removal 99.9%

## Operation

Touch-free infra-red activation

Hand dry time measurement: 10 seconds.

(Measurement based on National Sanitation Foundation Protocol P.335)

Operation lock-out period: 30 seconds

Airspeed at apertures: 430 mph

Operating airflow: Up to 30 l/s

## Logistics

Serial number prefix: Grey EB7; White EB8

Single unit order code:

Grey 25916-01; White 25917-01

Net weight: 8.2kg

Packaged weight: 10.6kg

Packaged dimensions: H735 × W359 × D304 mm

Unit barcode: Grey 5025 1550 1553 7; White 5025 1550 1554 4

## Standard guarantee

5 year parts, 1 year labour guarantee



## Product range

AB07 Grey

White



The Carbon Reduction Label is the registered trade mark of the Carbon Trust. HACCP International Non-food Certification Mark is the registered trade mark of the International HACCP Alliance. The NSF logo is the registered trade mark of NSF International.